

Overhead garage door system made of aluminium.

The silent runner among the garage doors.

Detolux is the ORIGINAL among the overhead doors with convincing comfort equipment. The door can be opened and closed comfortably from the inside of the car. At the push of a button on the radio remote control the Detolux garage door starts to move silently. The light integrated in the motor unit provides additional light inside the garage. The installation space requirement in the direct passage area can be minimized to 8 cm. The special roller locking devices guarantee a most quiet run.

Custom-made luxury garage door system made of aluminium. With closed bousing

At the present time there are very high demands regarding the locking of garages. As behind these openings there are usually valuable vehicles or objects. Therefore more and more building owners make the competent decision: Aluminium boxed roller doors with the brand name Resident. When the garage door is open, the curtain is inside the closed aluminium housing. Due to this construction the total area below the ceiling can be used as storage place of roof boxes, sports equipment or roof racks.



The Vertico lateral running door is an extraordinary solution to close garages in an intelligent way. It stands out by its high elegance, very small space requirement in the direct lintel area and best run properties. Its equipment comprising motor, radio remote control and obstacle detection gives proof of comfort and safety. As a special advantage two door openings can be programmed. That means, that Vertico can be opened completely or only

partly (passage door effect) depending on your needs.

The *aluminium* garage door profile, type CD 77

Roll-formed, double-wall aluminium hollow section profile for garage doors. With CFC-free insulating foaming. Thick-layer stove enamel with texture paint. Surface area 78,5 mm.

Can be combined with vision profiles CD 78.

CD 77 can be used for all door systems.



The *aluminium* garage door profile, type CD 200

Roll formed, double wall aluminium hollow section profile for roller shutters and garage doors. With CFC-free insulating foaming. Thick-layer stove enamel with texture paint. Surface area 55 mm. Profile CD 200 can only be used for Resident boxed roller doors.



Alulux... Experience the best quality! -5-